

This call closes the existing logical keyboard identified by the keyboard handle.

Syntax

KbdClose (KbdHandle)

Parameters

;KbdHandle ([HKBD](#)) - input: Default keyboard or the logical keyboard.

Return Code

;rc (USHORT) - return:Return code descriptions are: *0 - NO_ERROR *439 - ERROR_KBD_INVALID_HANDLE *464 - ERROR_KBD_DETACHED *504 - ERROR_KBD_EXTENDED_SG

Remarks

KbdClose blocks while another thread has the keyboard focus (by way of [KbdGetFocus](#)) until the thread with the focus issues [KbdFreeFocus](#). Therefore, to prevent KbdClose from blocking, it is recommended that KbdClose be issued only while the current thread has the focus. For example:

;KbdGetFocus:Wait until focus available on handle 0. ;KbdClose:Close a logical keyboard handle.
;KbdClose:Close another logical keyboard handle. ;KbdClose:Close still another logical keyboard handle. ;KbdFreeFocus:Give up the focus on handle 0.

Bindings

C

```
<PRE> #define INCL_KBD  
  
USHORT rc = KbdOpen(KbdHandle); PHKBD KbdHandle; /* Keyboard handle */ USHORT rc; /* return  
code */ </PRE>
```

MASM

```
<PRE> EXTRN KbdOpen:FAR INCL_KBD EQU 1  
  
PUSH@ WORD KbdHandle ;Keyboard handle CALL KbdOpen  
  
Returns WORD </PRE>
```

Kbd

From:

<http://185.82.219.184/doku/> - osFree wiki

Permanent link:

<http://185.82.219.184/doku/doku.php?id=en:docs:fapi:kbdclose&rev=1633521528>

Last update: **2021/10/06 11:58**

