

30

Brief

Rename file using FCB

Input

- DS:DX → modified FCB (see also [FCB](#)) the old filename ('?' wildcards OK) is in the standard location while the new filename ('?' wildcards OK, no drive) is stored in the 11 bytes beginning at offset 11h

Return

- AL = status
 - 00h successfully renamed
 - FFh no matching files,file is read-only, or new name already exists

Notes

subdirectories may be renamed using an extended FCB with the appropriate attribute, as may volume labels

See also

SVC API	
Supervisor calls	0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85
Structures	FCB XFCB FILETIME FILEDATE

2024/11/07 03:44 · prokushev · [0 Comments](#)

From: <http://www.osfree.org/doku/> - **osFree wiki**

Permanent link: <http://www.osfree.org/doku/doku.php?id=en:docs:mvm:api:30>

Last update: **2024/11/07 04:00**

