



This is part of **Win16 API** which allow to create versions of program from one source code to run under OS/2 and Win16. Under OS/2 program can be running under Win-OS/2 if program is Windows NE executable, and with help on Windows Libraries for OS/2, if it is OS/2 NE executable. [Here](#) is a WLO to OS/2 API mapping draft

2021/09/01 04:23 · prokushev · [0 Comments](#)

# CloseDriver

## Brief

Closes an installable driver.

## Syntax

```
LRESULT WINAPI CloseDriver(HDRVR hDriver, LPARAM IParam1, LPARAM IParam2);
```

## Parameters

- **hDriver**

Handle to the driver to close.

- **IParam1**

First close parameter.

- **IParam2**

Second close parameter.

## Return Code

Returns nonzero if successful or zero otherwise.

## Notes

The exact meaning of parameters depends on the driver.

## C Binding

```
CloseDriver(hDriver, 0, 0);
```

## MASM Binding

```
push lParam2  
push lParam1  
push hDriver  
call CloseDriver
```

## See also

[OPENDRIVER](#)

From:

<http://185.82.219.184/doku/> - **osFree wiki**

Permanent link:

<http://185.82.219.184/doku/doku.php?id=en:docs:win16:api:user:closedriver>

Last update: **2025/11/29 06:52**

