2025/11/05 08:54 1/3 KbdPeek

KbdPeek

Bindings: C, MASM

This call returns any available character data record from the keyboard without removing it from the buffer.

KbdPeek (CharData, KbdHandle)

CharData (**PKBDKEYINFO**) - output Address of the character data information:

asciicharcode (**UCHAR**) ASCII character code. The scan code received from the keyboard is translated to the ASCII character code.

scancode (**UCHAR**) Code received from the keyboard hardware.

status (**UCHAR**) State of the keystroke event:

Bit	Bit Description		
/-6	00	= Undefined.	
	01	= Final character, interim character flag off.	
	10	= Interim character.	
	11	= Final character, interim character flag on.	
5	1	= Immediate conversion requested.	
4-2		Reserved, set to zero.	
1	0	= Scan code is a character.	
	1	= Scan code is not a character; it is an extended key code from the keyboard.	
0	1	= Shift status returned without character.	

reserved (UCHAR) NLS shift status. Reserved, set to zero.

shiftkeystat (**USHORT**) Shift key status.

Bit	Description
15	SysReq key down
14	CapsLock key down
13	NumLock key down
12	ScrollLock key down
11	Right Alt key down
10	Right Ctrl key down
9	Left Alt key down
8	Left Ctrl key down
7	Insert on
6	CapsLock on
5	NumLock on
4	ScrollLock on
3	Either Alt key down
2	Either Ctrl key down
1	Left Shift key down

Last update: 2016/09/15 02:46

Bit Description
0 Right Shift key down

time (**ULONG**) Time stamp indicating when a key was pressed. It is specified in milliseconds from the time the system was started.

KbdHandle (**HKBD**) - input Default keyboard or the logical keyboard.

rc (**USHORT**) - return Return code descriptions are:

0	NO_ERROR
439	ERROR_KBD_INVALID_HANDLE
445	ERROR_KBD_FOCUS_REQUIRED
447	ERROR_KBD_KEYBOARD_BUSY
464	ERROR_KBD_DETACHED
504	ERROR_KBD_EXTENDED_SG

Remarks

On an enhanced keyboard, the secondary enter key returns the normal character 0DH and a scan code of E0H.

Double-byte character codes (DBCS) require two function calls to obtain the entire code.

If shift report is set with *KbdSetStatus* the *CharData* record returned, reflects changed shift information only.

Extended ASCII codes are identified with the status byte, bit 1 on and the ASCII character code being either 00H or E0H. Both conditions must be satisfied for the character to be an extended keystroke. For extended ASCII codes, the scan code byte returned is the second code (extended code). Usually the extended ASCII code is the scan code of the primary key that was pressed.

A thread in the foreground session that repeatedly polls the keyboard with *KbdCharln* (with no wait), can prevent all regular priority class threads from executing. If polling must be used and a minimal amount of other processing is being performed, the thread should periodically yield the CPU by issuing a *DosSleep* call for an interval of at least 5 milliseconds.

Family API Considerations

Some options operate differently in the DOS mode than in the OS/2 mode. Therefore, the following restrictions apply to *KbdPeek* when coding for the DOS mode:

- The *CharData* structure includes everything except the time stamp.
- Interim character is not supported.
- Status can be 0 or 1.
- KbdHandle is ignored.

C bindings

2025/11/05 08:54 3/3 KbdPeek

```
/* Scan Code */
 UCHAR
          chScan;
                             /* State of the character */
 UCHAR
          fbStatus:
                             /* Reserved (set to zero) */
 UCHAR
          bNlsShift;
 USH0RT
          fsState;
                             /* State of the shift keys */
                              /* Time stamp of keystroke (ms since ipl) */
 ULONG
          time;
}KBDKEYINFO;
#define INCL_KBD
USHORT rc = KbdPeek(CharData, KbdHandle);
PKBDKEYINFO
                CharData;
                               /* Buffer for data */
HKBD
                KbdHandle:
                               /* Keyboard handle */
USHORT
                               /* return code */068[068]
                 rc;
```

MASM bindings

```
KBDKEYINFO struc
  kbci chChar
                db ? ; ASCII character code
  kbci chScan
                db ? ;Scan Code
  kbci fbStatus db ? ;State of the character
  kbci bNlsShift db ? ; Reserved (set to zero)
  kbci fsState dw ? ; state of the shift keys
                dd ? ;time stamp of keystroke (ms since ipl)
  kbci time
KBDKEYINFO ends
EXTRN KbdPeek:FAR
INCL KBD
                   EQU 1
                            :Buffer for data
PUSH@
      0THER
              CharData
PUSH
      WORD
              KbdHandle
                            ;Keyboard handle
CALL
      KbdPeek
Returns WORD
```

From:

http://185.82.219.184/doku/ - osFree wiki

Permanent link:

http://185.82.219.184/doku/doku.php?id=en:ibm:prcp:kbd:peek

Last update: 2016/09/15 02:46

