

## MouClose

### Bindings: C, MASM

This call closes the mouse device for the current session.

#### *MouClose (DeviceHandle)*

*DeviceHandle (HMOU)* - input Mouse device handle from a previous MouOpen.

*rc (USHORT)* - return Return code descriptions are:

<b>0</b>	<b>NO_ERROR</b>
385	ERROR_MOUSE_NO_DEVICE
466	ERROR_MOU_DETACHED
501	ERROR_MOUSE_NO_CONSOLE
505	ERROR_MOU_EXTENDED_SG

### Remarks

**MouClose** closes the mouse device for the current session and removes the mouse device driver handle from the list of valid open mouse device handles.

### C bindings

```
#define INCL_MOU

USHORT rc = MouClose(DeviceHandle);

HMOU           DeviceHandle; /* Mouse device handle */
USHORT         rc;          /* return code */
```

### MASM bindings

```
EXTRN MouClose:FAR
INCL_MOU      EQU 1

PUSH WORD    DeviceHandle ;Mouse device handle
CALL MouClose

Returns WORD
```

From:  
<http://185.82.219.184/doku/> - osFree wiki



Permanent link:  
<http://185.82.219.184/doku/doku.php?id=en:ibm:prcp:mou:close>

Last update: **2016/09/15 03:13**