

MouClose

Bindings: C, MASM

This call closes the mouse device for the current session.

MouClose (**DeviceHandle**)

DeviceHandle (**HMOU**) - input Mouse device handle from a previous MouOpen.

rc (**USHORT**) - return Return code descriptions are:

0	NO_ERROR
385	ERROR_MOUSE_NO_DEVICE
466	ERROR_MOU_DETACHED
501	ERROR_MOUSE_NO_CONSOLE
505	ERROR_MOU_EXTENDED_SG

Remarks

[MouClose](#) closes the mouse device for the current session and removes the mouse device driver handle from the list of valid open mouse device handles.

C bindings

```
#define INCL_MOU

USHORT  rc = MouClose(DeviceHandle);

HMOU          DeviceHandle;  /* Mouse device handle */

USHORT        rc;            /* return code */
```

MASM bindings

```
EXTRN  MouClose:FAR
INCL_MOU          EQU 1

PUSH    WORD      DeviceHandle  ;Mouse device handle
CALL    MouClose

Returns  WORD
```

From:

<http://185.82.219.184/doku/> - **osFree wiki**

Permanent link:

<http://185.82.219.184/doku/doku.php?id=en:ibm:prcp:mou:close>

Last update: **2016/09/15 03:13**

