

MouFlushQue

Bindings: [C](#), [MASM](#)

This call directs the mouse driver to flush (empty) the mouse event queue and the monitor chain data for the session.

MouFlushQue (**DeviceHandle**)

DeviceHandle (**HMOU**) - input Mouse device handle from a previous [MouOpen](#).

rc (**USHORT**) - return Return code descriptions are:

0	NO_ERROR
385	ERROR_MOUSE_NO_DEVICE
466	ERROR_MOU_DETACHED
501	ERROR_MOUSE_NO_CONSOLE
505	ERROR_MOU_EXTENDED_SG

C bindings

```
#define INCL_MOU

USHORT  rc = MouFlushQue(DeviceHandle);

HMOU          DeviceHandle;  /* Mouse device handle */

USHORT        rc;            /* return code */
```

MASM bindings

```
EXTRN  MouFlushQue:FAR
INCL_MOU          EQU 1

PUSH    WORD      DeviceHandle  ;Mouse device handle
CALL    MouFlushQue

Returns  WORD
```

From:
<http://185.82.219.184/doku/> - **osFree wiki**

Permanent link:
<http://185.82.219.184/doku/doku.php?id=en:ibm:prcp:mou:flushque>

Last update: **2016/09/15 03:38**

